# Butler-Cote<sup>™</sup> Finish System

For Butler® Building Systems



# **Butler-Cote**<sup>™</sup> Finish System

## for Butler® Building Systems

All Butler-Cote<sup>™</sup> fluoropolymer finishes have a Solar Reflectance Index of 29 or greater.

## **Roof Systems**

## MR-24° AND CMR-24° ROOF SYSTEMS



## **VSRII** ROOF SYSTEM



For color, gauges, or color/panel combinations not shown, additional charges apply and a minimum order is required.



## **BUTLERIB® II ROOF SYSTEM**



## **MODULEZE™ II SOFFIT COLORS**













24 ga. 24 ga. 24 ga.

Cool Desert Beige 24 ga.



## Wall Systems

## SHADOWALL, BUTLERIB, II, STYLWALL, II FLAT AND FLUTED WALL SYSTEMS, AND MOD-36 (GABLE TRIM, EAVE TRIM, GUTTER AND DOWNSPOUTS)



## **BUTLER THERMAWALL** WALL SYSTEM



## **INTERIOR FINISH COLORS (NOT FORMULATED FOR EXTERIOR USE)**



wall, StylWall® II Fluted, Shadowall, MR-24, VSR II and MOD-36)

Thermawall & TextureWall ) USDA-approved

Liner and MOD-36 in 22 or 28 gauge only)

All color selections are close representations, but are limited by processing and viewing conditions.

Lead times may vary by product selection. Contact your Butler Builder® for more information.

## **GAUGE AVAILABILITY**

- Butlerib<sup>®</sup> II & Shadowall<sup>™</sup> 26 gauge
- StylWall® II Flat 26 gauge
- StylWall® II Fluted 24 gauge
- MOD-36 22, 24, 26, and 28 gauge
- Trim 26 gauge

\*Also available in 24 gauge for Butlerib® II, Shadowall™ and MOD-36

## A Commitment to Building Green

All standard Butler-Cote<sup>™</sup> 25-year fluoropolymer color finishes feature a Solar Reflectance Index (SRI) of 29 or greater.

## Enhance and Protect the Beauty

The standard exterior paint finish for all Butler panels and trim is the Butler-Cote system, consisting of a full strength 70% Kynar 500® or Hylar 5000® PVDF resin-base fluoropolymer finish.

The Butler-Cote system resists the chalking and fading that often leaves a building looking drab and dated. Our 25-year warranty guarantees that, on roof and wall panel standard colors, chalking will not exceed a rating of #8 and fading will not exceed  $5\Delta E$  color difference units. The warranty also covers peeling, cracks, or chipping of the paint finish.

While many manufacturers' warranties are prorated after a certain period of time, we offer our Butler-Cote roof and wall panel warranty for a full 25 years—with no prorating. It's a testament to our high performance standards.

# FLUOROPOLYMER FINISH VS. SILICONE POLYESTER AFTER 8 YEARS OF WEATHERING.



BUTLER-COTE" FINISH SYSTEM SOLAR REFLECTANCE DATA			
Available Standard "Cool" Colors	Initial Solar Reflectance	Initial Emittance	Solar Reflectance Index (SRI)
Cool Solar White	0.76	0.84	93
Cool Igloo White	0.64	0.84	76
Cool Ivory White	0.63	0.83	74
Cool Birch White	0.64	0.84	77
Cool Shell Gray	0.55	0.84	63
Cool Country Wheat	0.61	0.84	72
Cool Desert Beige	0.49	0.84	55
Cool Gray Stone	0.37	0.85	39
Cool Marsh Green	0.34	0.85	35
Cool Emerald Green	0.30	0.85	30
Cool Palm Green	0.30	0.84	29
Cool Ocean Blue	0.33	0.84	33
Cool Majestic Blue	0.30	0.84	29
Cool Brick Red	0.34	0.85	35
Cool Harvest	0.32	0.84	32
Cool Onyx Black	0.30	0.84	29
Galvalume® Plus	0.70	0.84	84



Butler Manufacturing Kansas City, MO 816-968-3000

www.butlermfg.com









Butler® building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Before finalizing project details, contact your nearest Butler Builder® or Butler Manufacturing for the latest information.

Kynar 500° is a registered trademark of Arkema. Hylar 5000° is a registered trademark of Solvay Solexis. USGBC logo is a registered trademark owned by the U.S. Green Building Council and is used by

permission.
© 2022 BlueScope Buildings North America, Inc. All rights reserved. Butler Manufacturing is a division of BlueScope Buildings North America, Inc. Find your independent Butler Builder® at www.butlermfg.com.
Form No. 4828 02/22